

THOMSON
*
DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

[Laid Open](#) [Vehicles](#) [Good Carriers](#)

[My Account](#) | [Products](#)

[Search: Quick/Number](#) [Boolean](#) [Advanced](#)

The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)

Tools: Add to Work File: [Create new Wo](#)

View: [INPADOC](#) | Jump to: [Top](#) ☒

[Email](#)

⌘ Title: **JP2002151034A2: SEPARATOR FOR SEALED LEAD ACID BATTER
SEALED LEAD ACID BATTERY USING THE SAME**

⌘ Country: **JP Japan**

⌘ Kind: **A2 Document Laid open to Public inspection I**

⌘ Inventor: **MATSUNAMI TAKAAKI;
SHIMIZU MAKOTO;
ENDO HIDEO;**

⌘ Assignee: **NIPPON MUKI CO LTD**
[News, Profiles, Stocks and More about this company](#)

⌘ Published / Filed: **2002-05-24 / 2000-11-13**

⌘ Application
Number: **JP2000000345742**

⌘ IPC Code: **H01M 2/16; H01M 10/06;**

⌘ Priority Number: **2000-11-13 JP2000000345742**

⌘ Abstract:

PROBLEM TO BE SOLVED: To provide a separator for a sealed lead acid battery which is formed by mixing inorganic powder in a dispersed state in a sheet of a minute glass fiber body obtained by a wet papermaking, in which a dendritic short circuit can be suppressed even if the interval between the plates is small, and an electrolytic solution in a high rate discharge can be effectively supplied to the plate side and a high rate discharge performance can be effectively improved as a result.

SOLUTION: This is the separator for a sealed lead acid battery in which inorganic powder is mixed at 15 to 30 wt.% in dispersed state in a sheet of a minute glass fiber body obtained by wet papermaking, and the inorganic powder is made to exist mixedly so as to gradually has a higher filling density from one surface side in the thickness direction of the separator toward the other surface side.

COPYRIGHT: (C)2002,JPO

⌘ Family: **None**

⌘ Other Abstract
Info: **None**



[Nominate](#)

[this for the Gallery...](#)

